



E		F	
REV(版本)	DESCRIPTION(描述)	NAME(名字)	DATE(日期)

- 技术指标:
- 塑件表面应光洁、无毛边、无明显收缩、缺陷、裂纹等现象.
 - 温度范围: -25° C~85° C.
 - 额定电压: 100V, AC/DC.
 - 接触电阻: ≤20mΩ.
 - 绝缘电阻: ≥1000MΩ.
 - 额定电流: 2A , AC/DC.



2 PIN 结构样式
(Structural style)



3 PIN 结构样式
(Structural style)

CKT	Dim A	Dim B	Dim C
2	2.00	4.90	8.00
3	4.00	6.90	10.00
4	6.00	8.90	12.00
5	8.00	10.90	14.00
6	10.00	12.90	16.00
7	12.00	14.90	18.00
8	14.00	16.90	20.00
9	16.00	18.90	22.00
10	18.00	20.90	24.00
11	20.00	22.90	26.00
12	22.00	24.90	28.00
13	24.00	26.90	30.00
14	26.00	28.90	32.00
15	28.00	30.90	34.00
16	30.00	32.90	36.00
17	32.00	34.90	38.00
18	34.00	36.90	40.00
19	36.00	38.90	42.00
20	38.00	40.90	44.00

序号	项目	描述	备注
1	塑胶	LCP	
2	端子	黄铜	
3	焊片	黄铜	
4	盖子		

深圳市兴成泰科技有限公司

品名 (TITLE)		制图 (DR)	
Pitch:2.00mm 立式带扣 SMT		XIAO	
料号 (DWG. NO)		校对 (CHKD)	
		Alex	
比例 (SCALE)		审核 (APPD)	
1:1			
单位 (UNITS)	mm	页码 (SHEET)	SIZE
		1 OF 1	A4
			REV
			A

一般公差 (TOLERANCE)
X ±.50 .XX ±.10
X ±.20 .XXX ±.05
ANGLES ±1°

